

Technical data for MiniSteam E (electrodes)

| Type | MSE05 | | MSE10 |
|---|--|-------------------|------------|
| Steam output [kg/h] | 4.4 - 4.8 | 4.8 - 5.2 | 9.5 - 10.4 |
| Electrical connection ⁽¹⁾ [V/Hz] | 220-240/1/N/50-60 | 380-415/3/N/50-60 | |
| Electrical power [kW] | 3.3 - 3.6 | 3.6 - 3.9 | 7.1 - 7.8 |
| Rated current [A] | 15.0 | 5.4 | 10.8 |
| Fuse [A] | 1 x 16 | 3 x 10 | 3 x 16 |
| Control voltage (internal) [V] | 220-240V/1/N | | |
| Weight (empty) [kg] | 15 | | |
| Weight (operating) [kg] | 20 | | |
| Dimensions WxHxD ⁽⁵⁾ [mm] | 595 x 390 x 255 | | |
| Water supply | 1 to 10 bar (100 x 10 ³ to 1000 x 10 ³ Pa), for 3/4" external thread | | |
| Waste water connection [mm] | in on-site drain | | |

Subject to technical changes.

⁽¹⁾ Other voltages upon request.

⁽⁵⁾ Outer width and depth dimensions.
Height including drain connection.

Our service for you

- HygroMatik distributors in more than 45 countries worldwide
- Technical hotline +49 4193 859 - 293 or hotline@hygromatik.com
- Manuals, planning tools and workshop offers are available online at www.hygromatik.com



HygroMATIK[®]
 WE HUMIDIFY THE AIR

HygroMatik GmbH
 Lise-Meitner-Str. 3
 24558 Henstedt-Ulzburg
 Germany

T +49 4193 895-0
 F +49 4193 895-33
hy@hygromatik.de
www.hygromatik.com