



Class
B-s1, d0
EN 13501-1

ALUAFS.70

Reaction to Fire.....	Difficult to Ignite
Operating Pressure.....	3000 Pa (maximum)
Temperature Range.....	- 30 °C / + 150 °C
Diameter Range.....	52 mm - 800 mm
Flexible Duct Construction	3 ply Aluminium + 2 ply Polyester
Flexible Duct Nominal Thickness.....	70 micron
Air Velocity.....	30 m/s (maximum)
Packing	Single cardboard box
Standard Length	10 m
Certificates.....	France M1, Europe EN ISO 11925-2 & EN 13823, Class B-s1, d0 Europe EN 13501-1, Class 0 BS 476 : Part 6 & 7



Class
B-s1, d0
EN 13501-1

ISOAFS.ALU70

Operating Pressure.....	3000 Pa (maximum)
Temperature Range.....	- 30 °C / + 150 °C
Diameter Range.....	52 mm - 800 mm
Jacket Construction	1 ply Aluminium + 2 ply Polyester
Jacket Nominal Thickness	45 micron
Flexible Duct Construction	3 ply Aluminium + 2 ply Polyester
Flexible Duct Nominal Thickness.....	70 micron
Air Velocity.....	30 m/s (maximum)
Insulation - Thickness - Density	Glasswool 25 mm - 16 kg/m ³
Packing.....	Single cardboard box
Standard Length	10 m
Certificates.....	France M1, Class B-s1, d0 Europe EN 13501-1



Class
B-s1, d0
EN 13501-1

SONOAFS.ALU70

Reaction to Fire.....	Difficult to Ignite
Operating Pressure.....	3000 Pa (maximum)
Temperature Range.....	- 30 °C / + 150 °C
Jacket Construction.....	1 ply Aluminium + 2 ply Polyester
Jacket Nominal Thickness	45 micron
Flexible Duct Construction	3 ply Aluminium + 2 ply Polyester
Air Velocity.....	30 m/s (maximum)
Insulation - Thickness - Density	Glasswool 25 mm - 16 kg/m ³
Packing.....	Single cardboard box
Standard Length.....	10 m
Certificates.....	France M1, Class B-s1, d0 Europe EN 13501-1

ΗΧΟΑΠΟΡΡΟΦΗΤΙΚΟΙ

